

Graphisoft Virtual Building Explorer User Guide

Graphisoft

Visit the Graphisoft website at <http://www.graphisoft.com> for local distributor and product availability information.

Graphisoft Virtual Building Explorer User Guide

Copyright © 2009 by Graphisoft, all rights reserved. Reproduction, paraphrasing or translation without express prior written permission is strictly prohibited.

Trademarks

ArchiCAD and Virtual Building Explorer are registered trademarks of Graphisoft.

Other product and company names are trademarks of the respective holders.

CONTENTS

| | |
|---|----|
| Introduction | 5 |
| Product Details..... | 5 |
| Workflow | 6 |
| Exporting ArchiCAD Models for VBE..... | 6 |
| Saving VBE Projects..... | 7 |
| Opening a VBE Project for Editing..... | 7 |
| Exploring a VBE Executable File..... | 7 |
| Interface | 8 |
| Menus..... | 8 |
| <i>FILE Menu</i> | 8 |
| <i>SETTINGS Menu</i> | 8 |
| <i>GLOBAL ILLUMINATION Menu</i> | 11 |
| <i>CONTROLS Menu</i> | 12 |
| <i>LAYERS Menu</i> | 14 |
| <i>GALLERY Menu</i> | 14 |
| Technical Notes | 16 |
| Texture Formats..... | 16 |
| <i>Alpha Channel Texture Effects</i> | 16 |
| Shadows..... | 16 |
| <i>Sun Shadow Artifacts</i> | 17 |
| Special Keyboard Shortcuts..... | 17 |
| SYSTEM REQUIREMENTS..... | 17 |
| <i>Operating System</i> | 17 |
| Installing the Virtual Building Explorer Package | 19 |
| Uninstalling the Virtual Building Explorer Package | 20 |
| License Management | 21 |
| | 22 |

Introduction

Graphisoft Virtual Building Explorer (VBE) allows architects to create photorealistic walk-through models from their ArchiCAD projects. With this new presentation tool, navigable 3D models can be saved as self-running executable files that also contain predefined fly-through animations and images of the building.

Product Details

The VBE package contains two components:

- 1) The **Virtual Building Export Add-on for ArchiCAD 12** allows the seamless export of ArchiCAD models directly into Virtual Building Explorer.
- 2) The **Virtual Building Explorer** is a standalone application to make live presentation environments of the imported ArchiCAD models and to save them as self-running executable files.

The product is available in two configurations:

- 1) **VBE** version with shaded OpenGL rendering engine
- 2) **VBE G** version with shaded OpenGL and Global Illumination rendering engines

Workflow

The standard workflow between ArchiCAD and VBE is the following:

- The Virtual Building model is created in ArchiCAD with the appropriate surface textures and materials applied on the building elements.
- Using the VBE export add-on for ArchiCAD, the 3D model is sent to the Graphisoft Virtual Building Explorer for further processing.
- The walk-through model is visualized in VBE and visualized with shadedOpenGL or global illumination (only in the VBEG version) engines. Preferred fly-through paths can also be defined and saved with the model.
- The VBE model is saved into a self-running executable file (.exe), which can be sent to the owners, builders and others parties for easy exploration of the project.

Exporting ArchiCAD Models for VBE

Once the Virtual Building model is created in ArchiCAD 12 and the proper surface textures are applied, the model is ready for export into VBE:

- 1) Open the project in AC12 and check the consistency of the model and the surface textures before starting the export process.

Note that you can't modify the 3D model and the surface materials in VBE.

- 2) Open the 3D window (perspective or axonometric views)
- 3) Launch the *File/ Export for Virtual Building Explorer* command
- 4) The *Export for Virtual Building Explorer* status window opens
- 5) Once the export process is finished, click on the *Launch* button
- 6) The VBE application starts automatically and the exported model is loaded into the program's memory

Saving VBE Projects

Once the AC model is exported into VBE, you can save the project in the native VBE.exe file format:

- 1) Press the *ESCAPE* key on your keyboard to access the VBE menus
- 2) Click on the *File/Save* command
- 3) Select the preferred project file location and enter the name of the VBE file
- 4) The VBE project is saved as a self-running executable (.exe) file

Opening a VBE Project for Editing

- 1) Start your VBE application. You need a full license of VBE to edit a project.
- 2) Open the *File* menu and click on the *Load* command
- 3) Select the preferred VBE.exe file to open it
- 4) Now you can start to edit the VBE project

Note that double-clicking on a VBE.exe file opens the project in non-editable mode.

Exploring a VBE Executable File

Click on the .exe file to explore the VBE model. The self-running executable file will install the VBE viewer application automatically. You don't need a commercial license of VBE to open these projects.

Interface

The VBE interface consists of the navigation window and the VBE menu. You can toggle between them with the ESCAPE key.

Menus

The following menus are available in Virtual Building Explorer:

- FILE
- SETTINGS
- GLOBAL ILLUMINATION
- LAYERS
- GALLERY
- CONTROLS
- INFO
- QUIT

FILE Menu

The file menu includes the standard I/O functions of the program. The *LOAD* command opens a VBE project (VBE.exe file) for editing. The *SAVE* command will store your project in the standard VBE self-running executable file (.exe) format.

SETTINGS Menu

The Settings dialog stores all the parameters that are related to the VBE model display and navigation control.

View Style

The VBE model can be displayed in the following view styles:

- Unlit
- Shaded
- Cartoon

-
- Shaded Cartoon
 - Global Illumination

The *Global Illumination* method give you the most realistic view of the model. This option is available only in the VBE_G version.

Note that you have to render the model with the Global Illumination engine before you can activate this view style.

Background

VBE offers the following background options:

- SKY (default VBE Sky image)
- WHITE
- GREY
- BLACK

In case you'd like to use custom skybox images, you have to replace the six .bmp files included in the *VirtualBuildingExplorer/Skybox* folder.

Stereo View

VBE can display the model in stereo view modes. The following methods are available:

- Left/Right
- RED/ CYAN
- OFF

Note that you need special stereo view glasses to enjoy this VBE feature.

Transparency

Value range: 20-80

The transparency of all translucent surfaces in the model is controlled by this parameter. Higher values result in less transparent surfaces.

View Cone

Value range: 10-120

Speed

Value range: 10-1000

This parameter defines the default speed of navigation. Higher numbers result in faster movement.

Note that you can temporary increase the navigation speed by holding down the ‘SHIFT’ button.

Mouse Invert

This option inverts the mouse navigation directions.

Additional Settings Menu commands

The following parameters are self-explanatory. The parameter value limits are shown in brackets.

Mouse Sensitivity (10-50)

Sun Altitude (10-80)

Sun Azimuth (0-360)

Sun Brightness (-100 - +100)

Camera Height (600-2000)

Camera Radius (150-400)

Greyscale ON/OFF

OpenGL Precision

This parameter affects the quality of shadows in the VBE viewer. Three methods are available:

- Fixed
- Float 1
- Float 2

The Fixed method results lower shadow quality but faster navigation speed. Most video cards support this method. We recommend that you set this option as a default for your VBE projects, since some video cards will not work with FLOAT methods.

More details about the OpenGL precision settings:

- **FIXED:** Shadows darken the model (-100 to 0); use simple edge filtering.
- **FLOAT 1:** Shadows darken or brighten the model (-100 to +100); uses softer edge filtering.
- **FLOAT 2:** Same as FLOAT 1, but overexposed pixels turn white instead of material-colored.

Help Popups

If this option is activated, a help popup window will appear over some of the Settings menu's commands.

It also controls if the introduction help-popup is displayed at the center of the screen when opening a VBE model.

GLOBAL ILLUMINATION Menu

This menu is available only if you have a VBEG license. In order to be able to view the model in Global Illumination mode, you have to render the model first. Choose *INITIALIZE* to prepare the model for Global Illumination view.

Note that this can be a lengthy process depending on the size of the model (number of triangles), the computer hardware (RAM, Video RAM, processor, Video Card type) and the Global Illumination options you choose. Initialization may fail if the model is too big since any single point on the model needs to be handled separately in the computer memory. The more graphics memory you have the larger model you can initialize.

Cancel the process by pressing ESCAPE. You can resume the process later. Completely lit surfaces are saved into project files and .exe files. When resuming the process, the starting point may roll back a few percent from where you cancelled.

Computing Light

This option affects the length of the Global Illumination calculation process.

- **LIGHT VIEW:** Lights surfaces visible from the current camera viewpoint.
- **LIGHT ALL:** Lights all surfaces.

Sample Accuracy

This option affects the length of the rendering process and the quality of the resulting images.

If your sample rate is lower than 1000-2000, try setting this to option to *LOW*. This will make shadow gradients less smooth and more pixelized, but will result in faster rendering.

Note: Changing sample accuracy will invalidate any previously computed light.

CONTROLS Menu

The CONTROLS menu displays the list of the basic navigation commands and their keyboard shortcuts. Most of these functions are self-explanatory and commonly used in first-person shooter computer games (FPS).

| Functions | Keyboard Shortcut |
|---------------|------------------------------|
| Menu | ESCAPE |
| Movement | W,S, A, D and the Arrow keys |
| Move Fast | SHIFT |
| Move Slow | CONTROL |
| Crouch | ALT |
| Jump | SPACE BAR |
| Lift | PAGE UP |
| Lower | PAGE DOWN |
| Fly Mode | F |
| Info Tool | I |
| Measure Tool | M |
| Outlines | O |
| Map Mode | BACKSPACE |
| Screenshot | F5 |
| Parallel View | F8 |

Info Tool

Pressing “**I**” during navigation activates the *Info Tool*. In this mode the cursor’s shape changes to a cross and the bounding box of the currently selected model element is highlighted. One click with the mouse opens the

Info palette, which shows basic information about the selected model element. The following information is displayed in the *Info Tool*:

- *Type* – Element Type (wall, slab etc.)
- *Layer* – Element Layer
- *Size* – Size of the element's bounding box
- *Volume* – Volume of the element
- *Floor Ind* – Index of the story in which the element is placed

Fly Mode vs. Walk Mode

The 'F' key toggles between Fly Mode and Walk Mode. The Walk Mode provides you with a more realistic viewing experience including the following features:

- *Opening recognition* to distinguish the solid building structures such as walls, columns and roofs from doors and windows during navigation
- *Gravity* to keep the camera height stable over slabs, ramps or stairs

Map Mode

This useful feature helps you to find your current position in the building during navigation. Press “*BACKSPACE*” during navigation to project the corresponding section of the floor plan over the current 3D view. Your current position and viewing direction is marked with a red arrow. Use the mouse wheel to zoom the map.

Measure Tool

Press 'M' to enable the measure tool. The three-dimensional distance from the camera to the world point at the center is computed and displayed as '*View Distance*'. To measure the distance between two three-dimensional points, click the left mouse button and pick two points. The resulting distance is computed and displayed as '*Measured Distance*'.

Screenshot

Press 'F5' to print the current view to a 24-bit .bmp file. The image will have the same resolution as your current viewport (your desktop resolution). The .bmp file will be saved with a unique name into the '*VirtualBuildingExplorer\Screenshot*' folder. When screenshots are printed

from a stand-alone .exe file, the images will be saved into the same directory as the .exe file.

Parallel View

Press 'F8' to enable the orthographic view. Use the mouse to rotate the model and the mouse wheel to zoom in/out. Hold down the right mouse button and move the mouse to pan over the model.

Note that Stereoscopic rendering is currently not supported in orthographic view.

INFO Menu

The Info Menu shows basic information about the active project and your VBE license:

- *Version*: The version and build number of your VBE application
- *License*: Type of your VBE license (full, trial, educational). It also displays whether you are using the global illumination version of VBE.
- *Triangle Count*: The models in VBE are made of 3D triangles. The speed of the 3D navigation and the memory usage by the VBE application are strongly affected by the number of triangles in the 3D model.
- *Video RAM Usage*: Displays the size of the Video RAM used by the project
- *RAM Usage*: Displays the size of the RAM used by the project

LAYERS Menu

The VBE project preserves the layers of the original ArchiCAD model. You can control the visibility of the model layers in the *Layers* dialog.

Note that layers are not available in global illumination mode.

GALLERY Menu

The Gallery menu accommodates the commands with which you can add pre-recorded walk-through clips and camera positions to your project.

Adding Camera Angles (positions) to your Project

To add camera angles press 'F4'

Recording Walk-through Clips

- To enter clip record mode: Press '*SHIFT*+*R*'.
- To start/stop recording: Click left mouse button.
- To exit clip record mode: Press '*SHIFT*+*R*'.

You must be in pause mode when exiting clip mode or you will lose that clip.

Both perspective mode and orthographic mode (F8) can be recorded.

Editing the Gallery

To change the order of the clips in the Gallery, press “*MOVE LEFT / MOVE RIGHT*”

Using the gallery

- Clips will playback in sequence if '*SEQUENCER*' is enabled, otherwise only the current clip will be played.
- Click the image to jump into that position or to play that clip.
- Press '*P*' to playback the current clip.
- Press '*Shift* + *P*' to playback the sequence of clips from the top.
- '*PLAY ON START*' will playback the sequence of clips as the .exe starts.
- '*PLAY ON IDLE*' will make playback start or continue screensaver-style.

Technical Notes

Texture Formats

VBE supports the following surface texture formats: jpg, bmp, tif, tga, png, gif.

If a texture would fail to load for any reason, the object that uses it will be drawn with the material color instead.

Alpha Channel Texture Effects

VBE supports alpha channel texture effects with 32-bit tif, tga and bmp images. For the alpha channel effects to be detected inside VBE, you must enable transparency in the ArchiCAD material/texture properties.

Shadows

Shadows in VBE are rendered using the OpenGL ARB_shadow extension. It works by rendering the scene, from the sun's point of view, into a texture map. This texture map is then projected onto the scene and OpenGL will determine whether a pixel is in shadow or not. Larger texture maps will produce higher quality shadows. The maximum size is determined by your graphics card (the graphics memory available and the maximum texture size allowed). Some graphics cards may have 256 MB on-board memory, but only allow a maximum texture size of 4096 x 4096. A shadow texture is typically 24-bit.

8192x8192 shadow texture will consume 200 MB of video memory.

4096x4096 shadow texture will consume 50 MB of video memory.

2048x2048 shadow texture will consume 12.5 MB of video memory.

VBE will automatically try to generate the largest possible shadow texture, starting with 8192x8192. Next, if this fails, it will try half that size, and so on.

The shadow's altitude, azimuth (heading) and brightness are controlled via the settings interface.

To turn off the sun shadows, set sun shadow brightness to a value near zero.

Sun Shadow Artifacts

Depending on the amount of available video card memory and the (physical) size of your model, the sun shadows may display artifacts. This is due to the fact that VBE cannot fit the whole model into the shadow map with good quality. Smaller models and more video graphics memory will improve the result.

Special Keyboard Shortcuts

- Holding down *Z* then pressing *ESCAPE* will quit.
- Holding down *SHIFT* and *CONTROL* at the same time will activate the light speed navigation, which is ten times faster than running
- Holding down the right mouse button while flying will make you stay on a fixed altitude. This is useful when recording a fly-over above a building, for example.
- Holding down the right mouse button while walking will lock the view horizontally for a perfectly straight perspective.

SYSTEM REQUIREMENTS

Operating System

Windows XP® Professional x32 and x64 Edition

Windows Vista® Ultimate, Business and Enterprise Edition

Software

ArchiCAD® 12 version (build 2420) or higher

Java 6 or later is required to run the installer.

CPU

Intel® Pentium 4 or higher

Multicore processor is recommended to exploit ArchiCAD 12 performance capabilities

RAM

1 GB of RAM is required

2 GB or more is recommended for complex models

Hard Drive

Minimum of 1 GB free hard disk space is required for a full installation.

Additional 2 GB is required for work with complex projects and 3D visualization.

Display

1280*1024 resolution or higher is needed to work with ArchiCAD. VBE supports 1024*768 or higher resolutions.

Video card

Open GL 1.4 and DirectX 9 compatible graphics card with 256 MB or more on-board video memory is recommended to fully exploit hardware acceleration capabilities.

To find compatibility data for video cards, please visit the following website:
http://archicadwiki.com/Video_Cards

Installing the Virtual Building Explorer Package

Important: When installing VBE, you must be logged on as a member of the Administrator Group.

Installing from CD:

After inserting the VBE Installation CD into your CD-ROM drive, the “Virtual Building Explorer Installation” screen will appear. Choose “Virtual Building Explorer” to install the VBE application and the “VB Export Add-On for ArchiCAD 12” option to install the ArchiCAD add-on. If the installer does not start automatically, double-click on the “Setup” application in the CD root directory.

Note: Java 6 is required to run the VBE Installer. If you do not have Java 6 installed on your system, it will be automatically installed when you begin installing ArchiCAD.

Uninstalling the Virtual Building Explorer Package

To uninstall the entire Virtual Building Explorer package, go to the Windows “Control Panel” and select “Programs and Features” (Vista) or “Add or Remove Programs” (XP). Find Virtual Building Explorer in the list of programs, and click the “Uninstall/Change” (Vista) or “Change/Remove” (XP) button. This will start the uninstaller, which will remove all program components from your computer, including the Virtual Building Export Add-on for ArchiCAD 12 and the Virtual Building Explorer application.

Important: Do not remove the Java Runtime Environment 6 before uninstalling VBE.

Please remember to deactivate your license before uninstalling the program.

License Management

Virtual Building Explorer is protected with a license key file. You must have a valid license key on your computer to be able to start VBE in full mode. License keys can be created and managed with the VBE License Manager application located in the VBE installation folder. To create the license key file, start the VBE License Manager, click on 'Activate', and enter the Serial Number and Password provided by your VBE distributor.

If you want to transfer your VBE license to other computers, please 'Deactivate' it first on the computer where you currently use VBE and then 'Activate' it on the new computer.

Note that there is a daily limit on the license management trials on one computer.

Please remember to deactivate your license before uninstalling VBE.

